

EOS Production Sites Network Performance Report: June 2012

This is a monthly summary of EOS network performance testing between production sites -- comparing the measured performance against the requirements. **Significant improvements are noted in Green, Network problems in Red, System problems and Requirements issues in Gold, Issues in Orange, and other comments in Blue.**

Highlights:

- **Mostly stable flows**
 - **GPA 3.53** (was 3.64 last month).
- **Requirements:** updated to use the Network Requirements Database
 - Previously used Handbook 1.4.3 (since May '09)
- **All EBnet Outflows:** Continued high packet loss and reduced thruput started 29 February. Partial improvement observed in May.
- **LaRC ASDC Outflow:** very high congestion reduced performance on most outflows. (Not observed from LaRC ANGe or LaRC-PTH)
- **3 flows below "Good":**
 - GSFC MODAPS-PDR → EROS ("Low")
 - LaRC ASDC → JPL ("Adequate")
 - GSFC NPP → Wisconsin ("Adequate")

Ratings Changes:

Upgrade: ↑ GSFC → JPL: **Good** → **Excellent** (requirement reduced)

Downgrades: ↓

GSFC NPP → Wisconsin: **Good** → **Adequate** (requirement increased)


GSFC → KNMI: **Excellent** → **Good** (requirement increased)

Ratings Categories:

Rating	Value	Criteria
Excellent:	4	Total Kbps > Requirement * 3
Good:	3	1.3 * Requirement <= Total Kbps < Requirement * 3
Adequate:	2	Requirement < Total Kbps < Requirement * 1.3
Almost Adequate:	1.5	Requirement / 1.5 < Total Kbps < Requirement
Low:	1	Requirement / 3 < Total Kbps < Requirement / 1.5
Bad:	0	Total Kbps < Requirement / 3

Where Total Kbps = Average Integrated Kbps (where available), otherwise just iperf

Note that "**Almost Adequate**" implies meeting the requirement except for the 50% contingency factor.

Ratings History:

The chart above shows the number of sites in each rating category since EOS Production Site testing started in September 1999. Note that these ratings do NOT relate to absolute performance – they are relative to the EOS requirements.

Additions and deletions:

2011 April: Added RSS to GHRC
 2011 May: Deleted WSC to ASF for ALOS
 2012 January: Added NOAA → GSFC-SD3E
 Added GSFC-SD3E → Wisconsin
 2012 June: Deleted GSFC → LASP
 Deleted GSFC ← → JAXA

Requirements Basis:

This month, the requirements have been switched, as planned for quite a while, to use the EOSDIS network requirements database. ESDIS has been reviewing its network ICD's with each of the instrument teams. These ICDs are now essentially completed, and the database has been updated with the ICD values, so those values are now used here.


Until now, the requirements were based on the EOS Networks Requirements Handbook, Version 1.4.3 (from which the original database requirements were derived). Prior to that, the requirements were derived from version 1.4.2.

One main difference between Handbooks 1.4.2 and 1.4.3 is that most flows which occur less than once per day were averaged over their production period. These flows were typically monthly Level 3 data transfers, which were specified to be sent in just a few hours. However, they could easily be accommodated either between the per-orbit flows, or within the built-in contingency. Previously, these flows were added in linearly to the requirements, making the requirements unrealistically high.

Additionally, the contingency for reprocessing flows greater than 2X reprocessing was reduced. These flows WERE a major component of the contingency, so adding additional contingency on top of these flows was considered excessive.


Integrated Charts:

Integrated charts are included with site details, where available. These charts are “Area” charts, with a “salmon” background. A sample Integrated chart is shown here. The yellow area at the bottom represents the daily average of the user flow from the source facility (e.g., GSFC, in this example) to the destination facility (JPL, in this example) obtained from routers via “netflow”. The green area is stacked on top of the user flow, and represents the “adjusted” daily average iperf throughput between the source-destination pair most closely corresponding to the requirement. This iperf measurement essentially shows the circuit capacity remaining with the user flows active. Adjustments are made to compensate for various systematic effects, and are best considered as an approximation. The red line is the requirement for the flow from the source to destination facilities. On some charts a blue area is also present – usually “behind” the green area – representing adjusted iperf measurements from a second source node at the same facility.




Network Requirements vs. Measured Performance

June 2012		Requirements (mbps)		Testing				Ratings		
Source → Destination	Instrument (s)	Current	Old	Source → Dest Nodes	Average User Flow mbps	iperf Median mbps	Integrated mbps	Ratings re Database Requirements		
		Database	HB 1.4.3+					This Month	Last Month	
GSFC → EROS	MODIS, LandSat	548.4	342.9	MODAPS-PDR → EROS LPDAAC	24.7	184.3	193.1	Low	Low	
GSFC → JPL	AIRS, MLS, NPP, ISTs	58	116.7	GSFC GES DISC → JPL-AIRS	90.4	149.9	176.0	Excellent	Good	
JPL → GSFC	MLS	0.57	0.6	JPL-PODAAC → GSFC GES DISC	3.3	81.3	82.4	Excellent	Ex	
JPL → RSS	AMSR-E	0.16	0.5	JPL-PODAAC → RSS (Comcast)		18.8		Excellent	Ex	
RSS → GHRC	AMSR-E	0.32	0.3	RSS (Comcast) → GHRC		3.7		Excellent	Ex	
LaRC → JPL	TES, MISR	83.5	69.3	LARC-ASDC → JPL-TES	21.2	95.8		Adequate	Adq	
JPL → LaRC	TES	1.1	1.5	JPL-TES → LARC-PTH	2.0	211.6		Excellent	Ex	
GSFC → LaRC	CERES, MISR, MOPITT, TES, MODIS	52.2	31.3	GES DISC → LaRC ASDC	21.8	561.2	561.7	Excellent	Ex	
LaRC → GSFC	MISR	0.6	0.4	LARC-ASDC → GES DISC	0.63	461.4	461.4	Excellent	Ex	
JPL → NSIDC	AMSR-E	0.16	0.2	JPL-PODAAC → NSIDC		44.3		Excellent	Ex	
NSIDC → GSFC	AMSR-E, MODIS, ICESAT	0.017	0.6	NSIDC DAAC → GES DISC	3.9	230.4	231.7	Excellent	Ex	
GSFC → NSIDC	AMSR-E, MODIS, ICESAT	8.42	27.6	GES DISC → NSIDC-DAAC	1.32	112.9	112.9	Excellent	Ex	
GHRC → NSIDC	AMSR-E	0.46	0.5	GHRC → NSIDC DAAC (ftp)	0.22	4.0		Excellent	Ex	
NOAA → GSFC	NPP	522.3	615.6	NOAA-PTH → GSFC NPP-SD3E OPS1	321.5	915.9	972.1	Good	Good	
GSFC → WISC	NPP	259.1	253.7	GSFC NPP-SD3E OPS1 → WISC	195.0	266.7	316.3	Adequate	Good	
LaRC → NCAR	MOPITT	0.044	0.1	LaRC-PTH → NCAR		154.5		Excellent	Ex	
GSFC → JAXA	TRMM, AMSR-E, MODIS	3.51	0.1	GSFC → JAXA	3.54	Testing discontinued:		n/a	Ex	
JAXA → GSFC	AMSR-E	0.16	0.1	JAXA → GSFC	0.11	31 March 2009		n/a	Ex	
GSFC → ERSDAC	ASTER	6.75	5.4	GSFC-EDOS → ERSDAC	4.3	40.7	42.5	Excellent	Ex	
ERSDAC → EROS	ASTER	8.3	8.3	ERSDAC → EROS PTH	4.0	90.3	91.4	Excellent	Ex	
GSFC → KNMI	OMI	13.4	0.03	GSFC-OMISIPS → KNMI ODPS	1.8	35.0	35.6	Good	Ex	
		Significant change from HB v1.4.3 to Requirements Database								
		Value used for ratings								
*Criteria:	Excellent	Total Kbps > Requirement * 3						Ratings Summary		
	Good	1.3 * Requirement <= Total Kbps < Requirement * 3						Database Req		
	Adequate	Requirement < Total Kbps < Requirement * 1.3						Score	Prev	
	Almost Adequate	Requirement / 1.5 < Total Kbps < Requirement						Excellent	14	17
	Low	Requirement / 3 < Total Kbps < Requirement / 1.5						Good	2	3
	Bad	Total Kbps < Requirement / 3						Adequate	2	1
								Almost Adequate	0	0
								Low	1	1
								Bad	0	0
								Total Sites	19	22
Notes:	Flow Requirements include:									
	TRMM, Terra, Aqua, Aura, ICESAT, QuikScat, GEOS, NPP							GPA	3.53	3.64
								</		



This new chart shows the averages for the main EOS production flows for the current month. Up to date flow information can be found at http://ensight.eos.nasa.gov/Weather/web/hourly/Production_Flows-A.shtml

This graph shows a bar for each source-destination pair – relating the measurements to the requirements for that pair. The bottom of each bar represents the average measured user flow from the source site to the destination site (as a percent of the requirement) – it indicates the relationship between the requirements and actual flows. Note that the requirements generally include a 50% contingency factor above what was specified by the projects, so a value of 67% (dotted orange line) would indicate that the project is flowing as much data as requested. The top of each bar similarly represents the integrated measurement, combining the user flow with Iperf measurements – this value is used to determine the ratings.



1) EROS:

Ratings: GSFC → EROS: Continued **Low**
 ERSDAC → EROS: Continued **Excellent**

Web Page: <http://ensight.eos.nasa.gov/Organizations/production/EROS.shtml>
http://ensight.eos.nasa.gov/Organizations/production/EROS_PTH.shtml

Test Results:

Source → Dest	Medians of daily tests (mbps)			User Flow	Integrated
	Best	Median	Worst		
MODAPS-PDR → EROS LPDAAC	263.1	184.3	123.7	24.7	193.1
GSFC-EDOS → EROS LPDAAC	116.3	63.6	24.9		
GES DISC → EROS LPDAAC	320.1	268.7	164.3		
GSFC-ENPL → EROS LPDAAC	407.9	386.4	248.5		
ERSDAC → EROS LPDAAC	124.6	90.3	57.4	4.0	91.4
NSIDC SIDADS → EROS PTH	126.9	47.7	15.9		
GSFC-ENPL → EROS PTH	803.7	707.8	581.1		
GSFC-NISN → EROS PTH	513.0	318.0	163.4		
LaRC PTH → EROS PTH	188.8	169.6	112.2		

Requirements:

Source → Dest	Date	mbps	prev	Rating
GSFC → EROS	CY '12 -	548.4	343	Low
ERSDAC → EROS	FY '06 -	8.33	8.3	Excellent

Comments:

1.1 GSFC → EROS: The rating is based on the MODAPS-PDR Server to EROS LP DAAC measurement, since that is the primary flow. The requirement was switched this month, from using the Handbook v1.4.3 to now use the requirements database. This resulted in a 60% increase in the requirement, based primarily on increased MODIS reprocessing. As MODIS is not conducting reprocessing at present, the user flow this month is only about 4.5% of the new requirement.

The route is via the Doors to NISN SIP, via the NISN 10 gbps backbone to the NISN Chicago CIEF, then via GigE to the StarLight Gigapop, peering there with the EROS OC-48 tail circuit.




Due to packet loss on all flows leaving EBnet, the median integrated thrupt from MODAPS-PDR to LPDAAC is again below the requirement, even without the 50 % contingency factor, so the rating remains **Low**. From GES DISC (also on EBnet) to LPDAAC, the thrupt is better, but would also be rated **Low** vs. the increased requirement (but “**Almost Adequate**” vs. the old requirement).

Iperf testing for comparison is performed from GSFC-ENPL to both LPDAAC and to EROS-PTH. The GSFC-ENPL host has a direct 10 gig connection to the MAX; its route is via MAX to Internet2 to StarLight in Chicago. GSFC-ENPL to EROS-PTH typically gets about 700 mbps, and shows the capacity of the network is in excess of the requirement – it would be rated **Adequate** (almost “**Good**”). Also, GSFC-ENPL to EROS LPDAAC is the best to LPDAAC, and would be rated “**Almost Adequate**”. The difference in performance from GSFC-ENPL to EROS-PTH vs LPDAAC is attributable to the extra firewalls at EROS.

1.2 ERSD → EROS: **Excellent**. See section 9 (ERSD) for further discussion.

1.3 NSIDC → EROS-PTH: Performance dropped substantially in early June (median was 333 mbps in May). Other tests to and from NSIDC dropped at the same time, so the problem is believed not to be related to EROS.

1.4 LaRC → EROS: The thrupt from LaRC-PTH to EROS-PTH was stable. The route is via NISN SIP to the Chicago CIEF to StarLight – similar to EBnet sources.



2) to GSFCRatings: NOAA → NPP SD3E: **Good**NSIDC → GES DISC: Continued **Excellent**LDAAC → GES DISC: Continued **Excellent**JPL → GSFC: Continued **Excellent**

Web Pages:

http://ensight.eos.nasa.gov/Missions/NPP/GSFC_SD3E.shtml<http://ensight.eos.nasa.gov/Organizations/production/GDAAC.shtml>http://ensight.eos.nasa.gov/Organizations/production/ESDIS_PTH.shtmlhttp://ensight.eos.nasa.gov/Missions/icesat/GSFC_ISIPS.shtml**Test Results:**

Source → Dest	Medians of daily tests (mbps)			User Flow	Integrated
	Best	Median	Worst		
NOAA-PTH → NPP-SD3E-OPS1	937.9	915.9	775.7	321.5	972.1
EROS LPDAAC → GES DISC	221.8	196.6	132.6		
EROS PTH → GSFC-ESDIS PTH	420.1	282.6	165.7		
JPL-PTH → GSFC-ESDIS PTH	88.0	85.4	79.6	3.0	
JPL-TES → GSFC-NISN	585.7	172.3	31.5		
LaRC ASDC → GES DISC	562.2	461.4	29.1	0.63	
LARC-ANGe → GSFC-ESDIS PTH	505.0	424.2	340.8		
NSIDC DAAC → GES DISC	253.3	230.4	177.0	3.9	
NSIDC DAAC → GSFC-ISIPS (scp)	56.5	43.1	20.8		

Requirements:

Source → Dest	Date	Mbps	Prev	Rating
NSIDC → GSFC	CY '12 –	0.017	0.6	Excellent
LaRC ASDC → GES DISC	CY '12 –	0.6	0.4	Excellent
JPL → GSFC combined	CY '12 –	0.57	3.2	Excellent
NOAA → NPP SD3E	CY '12 –	522.3	615.6	Good

Comments: Note: all requirements were updated this month...see above.





NOAA → NPP-SD3E: Performance from NOAA-PTH to GSFC NPP-SD3E-OPS1 was very steady at over 900 mbps, limited by the gig-E interfaces on the test machines (the circuits are all 10 gbps). User flow was similar to last month, and close to expectations soon after NPP launch.

EROS, EROS-PTH → GSFC: The thrupt for tests from EROS and EROS-PTH to GES DISC and ESDIS-PTH were mostly stable.

JPL → GSFC: Thrupt from JPL-PTH was again very stable this month, limited by the Fast-E interface on JPL-PTH. With the modest requirement the rating remains “Excellent”. The actual user flow is closer to the old, and above the new, reduced requirement. Testing from JPL-TES to GSFC-NISN (not graphed) more clearly shows the capability of the network.

LaRC → GSFC: Performance from LaRC ASDC to GES DISC was again very variable, apparently due to congestion at ASDC. Thrupt from LaRC ANGe to ESDIS-PTH was much more stable. Both results remained way above 3 x the modest requirement, so the rating continues as “Excellent”. The user flow this month was very close to the requirement.

NSIDC → GSFC: Performance from NSIDC to GES DISC was steady, and way above the requirement; the rating remains “Excellent”. The user flow was again above the old requirement, and well above the new lower requirement. Testing to GSFC-ISIPS was restored in May by using SCP (iperf testing still down after reconfiguration due to firewall blocking). SCP thrupt is lower than iperf previously, as expected, but meets the requirement.



2.2 GSFC-ECHO: EOS Metadata Clearinghouse

Web Page: http://ensight.eos.nasa.gov/Organizations/gsfcs/GSFC_ECHO.shtml

Test Results:



Source	Medians of daily tests (mbps)		
	Best	Median	Worst
EROS LPDAAC	92.9	92.0	80.3
EROS LPDAAC ftp	12.3	11.8	9.5
GES DISC	93.7	93.3	91.6
GES DISC ftp	92.5	91.4	72.3
LaRC ASDC DAAC	93.5	93.2	28.4
LaRC ASDC DAAC ftp	n/a	n/a	n/a
NSIDC DAAC	46.5	46.4	45.4
NSIDC DAAC ftp	11.5	11.2	5.9

Comments:

The echo node was moved at the end of September '11. Most ftp tests continued working (except from LaRC ASDC), but iperf tests needed new firewall rules before resumption of testing – this was fixed in June (Iperf testing resumed from GES DISC in November).

In late January, however, throughput from GES DISC to ECHO dropped to just under 100 mbps, suggesting that a fast-E interface was in use. Performance returned to the higher state for the first week in March: iperf from GES DISC was back over 500 mbps, but the ftp stopped working during that period. Then, by March 7, the 100 mbps limitation was back – but the ftp tests from EROS and NSIDC started working again.

Performance was stable from EROS and NSIDC. FTP performance is mostly limited by TCP window size – especially from sites with long RTT.



2.3 GSFC-EMS: EOS Metrics System

Web Page: http://ensight.eos.nasa.gov/Organizations/gsfcs/GSFC_EMS.shtml

Test Results:


	Medians of daily tests (mbps)		
	Best	Median	Worst
EROS LPDAAC	274.3	248.1	151.5
GES DISC	621.9	570.9	213.0
LARC ASDC	487.3	403.8	12.0
MODAPS-PDR	936.8	933.6	767.1
NSIDC-SIDADS	251.2	138.6	34.1

Comments:

Testing is performed to GSFC-EMS from the above nodes, iperf only. The testing was transitioned to the new EMS test node (FS1) between November '11, and January '12 with much improved throughput. The performance limitation to the old server was its 100 mbps Fast-E connection; the new server is gigabit connected.

Throughput from LARC ASDC is very noisy, similar to other destinations from LARC ASDC (Last month's best and median are similar, but the worst was 82 mbps – suffering from congestion even then).

Also, throughput from NSIDC-SIDADS decreased and became noisier, as did other NSIDC performance.



3) JPL:

3.1) GSFC → JPL:

Ratings: GSFC → JPL: ↑ **Good** → **Excellent**

Web Pages: http://ensight.eos.nasa.gov/Missions/aqua/JPL_AIRS.shtml
http://ensight.eos.nasa.gov/Missions/aura/JPL_MLS.shtml
http://ensight.eos.nasa.gov/Organizations/production/JPL_QSCAT.shtml
http://ensight.eos.nasa.gov/Organizations/production/JPL_PODAAC.shtml

Test Results:

Source → Dest	Medians of daily tests (mbps)			User Flow	Integrated
	Best	Median	Worst		
GSFC-GES DISC → JPL-AIRS	187.4	149.9	95.8	90.4	176.0
NPP-SD3E-OPS2 → JPL-AIRS	161.6	117.8	78.7		
GSFC-NISN → JPL-AIRS	195.9	180.4	142.3		
ESDIS-PTH → JPL-AIRS	213.0	152.9	101.3		
ESDIS-PTH → JPL-PODAAC	138.5	104.7	73.2		
GSFC-NISN → JPL-PODAAC	116.2	85.0	34.4		
MODAPS-PDR → JPL-PODAAC	61.3	44.5	27.5		
GSFC-NISN → JPL-QSCAT	74.4	71.0	58.1		
ESDIS-PS → JPL-QSCAT	46.0	29.7	19.4		
GSFC-NISN → JPL-MLS	222.5	160.4	115.8		
ESDIS-PTH → JPL-MLS	201.5	128.2	64.4		

Requirements:

Source → Dest	Date	Mbps	Prev	Rating
GSFC → JPL Combined	CY '12-	58	116.7	Excellent
GSFC → JPL AIRS	CY '12-	40	98	Excellent
GSFC NPP → JPL Sounder	CY '12-	15	15	Excellent
GSFC → JPL MLS	CY '12-	1.0	2.1	Excellent

Comments: Due to EBnet outgoing packet loss, throughput from all EBnet sources (GES DISC, NPP-SD3E, ESDIS-PS, and ESDIS-PTH) dropped significantly on 29 February, compared with GSFC-NISN, which was stable. Throughput from GES DISC and ESDIS-PTH mostly improved in late April.

AIRS, Overall: The requirements were switched this month, to use the requirements database, instead of the Handbook v1.4.3 previously. This resulted in a 50% decrease in the overall requirement.






The AIRS and thus overall Integrated throughput from GES DISC was stable, and is now above 3 x the reduced AIRS requirement, so the AIRS rating improves to **Excellent**. The **JPL overall rating** is based on this test compared with the sum of all the GSFC to JPL requirements – the throughput is now [very slightly] above 3 x this requirement, so the overall rating also improves to **Excellent**. Note that the actual user flow was close to the old requirement, and well above the new one.

NPP: Testing from SD3E-OPS2 is also to JPL-AIRS, as a proxy for JPL-Sounder PEATE. Throughput was comparable to other EBnet sources, well in excess of the requirement.

PODAAC: Performance to PODAAC is way above the 1.5 mbps PODAAC requirement, rating **Excellent**.

QSCAT: Throughput from ESDIS-PS to QSCAT is noisy due to EBnet packet loss. (unlike from GSFC-NISN, which was more stable). It remains well above the modest requirement, rating **Excellent**.

MLS: Throughput from ESDIS-PTH is low due to EBnet packet loss. Throughput from GSFC-NISN was stable. Both were way above the modest requirement, so the rating remains **Excellent**.



3.2) LaRC → JPLRating: Continued **Adequate**

Web Pages:

http://ensight.eos.nasa.gov/Organizations/production/JPL_TES.shtmlhttp://ensight.eos.nasa.gov/Missions/terra/JPL_MISR.shtmlhttp://ensight.eos.nasa.gov/Organizations/production/JPL_PTH.shtml**Test Results:**

Source → Dest	Medians of daily tests (mbps)			User Flow	Integrated
	Best	Median	Worst		
LaRC DAAC → JPL-TES	102.5	95.8	23.0	0.09	
LaRC PTH → JPL-TES	160.9	143.5	132.2		
LaRC PTH → JPL-TES sftp	26.5	25.8	20.8		
LaRC ANGE → JPL-PTH	77.8	75.1	69.0	13.3	
LaRC DAAC → JPL-MISR	56.9	50.7	8.9	9.8	51.8
LaRC PTH → JPL-MISR	70.0	63.8	25.5		

Requirements:

Source → Dest	Date	Mbps	Prev	Rating
LaRC → JPL-Combined	CY '12 –	83.5	69.3	Adequate
LaRC DAAC → JPL-TES	CY '12 –	5.5	7.0	Excellent
LaRC DAAC → JPL-MISR	CY '12 –	78.1	62.3	Almost Adq.







Note: The overall LaRC → JPL flow (13.3 mbps) returned close to normal – it was much higher than normal last month. 74% of that flow this month was for MISR. The JPL-PTH integrated graph shows the overall LaRC to JPL user flow (vs. the overall requirement).

Performance from LaRC ASDC to JPL was very variable (typically on a 3 hour cycle), beginning at the end of April, apparently due to congestion at ASDC. Performance from LaRC ANGE and LaRC PTH to JPL did not exhibit this characteristic, and was much more stable.

LaRC → JPL (Overall, TES): Median performance from LaRC ASDC DAAC to JPL-TES dropped way down as a result of the above congestion. It remains over 3 x the TES requirement, so the TES rating remains “**Excellent**”. But is now only 15% above the increased combined requirements, so the Overall rating remains **Adequate**. User flow to TES is very low.

LaRC → JPL (MISR): There was an increase in user flow to MISR of about 40 mbps during the first part of May – the iperf thrupt showed a corresponding decrease. The integrated thrupt is limited by the Fast-E connection to the MISR node, and the ASDC congestion, and the median is now only 65% of the requirement, so the rating remains **Almost Adequate**.

Note: Even though the LaRC → MISR rating is “**Almost Adequate**”, the overall LaRC → JPL rating remains “**Adequate**”, since the MISR performance is limited by MISR’s Fast-E interface. Its performance is therefore not representative of the overall LaRC → JPL capability.




3.3) JPL → LaRCRating: Continued **Excellent**Web Page: http://ensight.eos.nasa.gov/Organizations/production/LARC_PTH.shtml**Test Results:**

Source → Dest	Medians of daily tests (mbps)			User Flow
	Best	Median	Worst	
JPL-PTH → LaRC PTH	83.3	59.5	57.3	2.0
JPL-TES → LaRC PTH	295.0	211.6	104.3	

Requirements:

Source → Dest	Date	Mbps	Prev	Rating
JPL → LaRC	CY '12 –	1.1	1.5	Excellent



Comment: This requirement is primarily for TES products produced at the TES SIPS at JPL, being returned to LaRC for archiving. This month the thrupt from JPL-TES was much higher than the requirement; the rating remains “**Excellent**”. The user flow was closer to usual and the requirement this month.

Thruput from JPL-PTH to LaRC-PTH was again mostly at the lower of its two common states – 63 and 85 mbps, limited by a Fast-E interface on JPL-PTH.

4) GSFC → LaRC:Rating: Continued **Excellent**

Web Pages : <http://ensight.eos.nasa.gov/Organizations/production/LARC.shtml>
http://ensight.eos.nasa.gov/Organizations/production/LARC_ANGe.shtml
http://ensight.eos.nasa.gov/Organizations/production/LARC_PTH.shtml

Test Results:

Source → Dest	Medians of daily tests (mbps)			User Flow	Integrated
	Best	Median	Worst		
GES DISC → LaRC ASDC	601.6	561.2	392.6	21.8	561.7
GSFC-EDOS → LaRC ASDC	298.3	142.8	57.3		
ESDIS-PTH → LaRC-ANGe	402.1	340.0	251.2		
GSFC-NISN → LaTIS	490.4	432.7	272.7		

Requirements:




Source → Dest	Date	Mbps	Prev	Rating
GSFC → LARC (Combined)	CY '12 –	52.2	31.3	Excellent

Comments: Due to EBnet outgoing packet loss, thrupt from all EBnet sources (GES DISC, EDOS, and ESDIS-PTH) dropped significantly on 29 February, compared with GSFC-NISN, which was stable. Thrupt from GES DISC mostly recovered in May. Note that packet loss does not have much effect on thrupt for these flows – TCP recovers quickly due to the short RTT.

GSFC → LaRC ASDC: Thrupt from GES DISC to LaRC ASDC DAAC remained well above 3 x the increased combined requirement, so the rating remains “**Excellent**”. Thrupt to ASDC from GSFC-EDOS was much lower than from GES DISC.

As seen on the integrated graph, there were periods of high user flow exceeding the requirement in both May and June.

ANGe (LaTIS): Testing to ANGe from ESDIS-PTH dropped in March due to EBnet packet loss. Testing to LaTIS (Darrin) from GSFC-NISN was better, with consistent results.



5) Boulder CO sites:

5.1) NSIDC:

Ratings: GSFC → NSIDC: Continued **Excellent**
 JPL → NSIDC: Continued **Excellent**
 GHRC → NSIDC: Continued **Excellent**

Web Pages: <http://ensight.eos.nasa.gov/Organizations/production/NSIDC.shtml>
http://ensight.eos.nasa.gov/Organizations/production/NSIDC_SIDADS.shtml
http://ensight.eos.nasa.gov/Organizations/production/NSIDC_PTH.shtml

Thruput from some (but not all) sources to NSIDC destinations dropped dramatically at the end of May. But no corresponding change in route or packet loss was observed! (It is suspected that the problem might relate to the return route.)

Test Results: NSIDC S4PA

Source → Dest	Medians of daily tests (mbps)			User Flow	Integrated
	Best	Median	Worst		
GES-DISC → NSIDC DAAC	132.6	112.9	74.9	1.3	124.4
MODAPS-PDR → NSIDC DAAC	32.4	28.2	23.1		
GSFC-EDOS → NSIDC DAAC	17.7	14.7	10.6		
GSFC-ISIPS → NSIDC (iperf)	65.0	46.6	28.9		
JPL PODAAC → NSIDC DAAC	49.8	44.3	27.9		
GHRC → NSIDC DAAC (nuttcp)	6.39	4.00	3.16		
GHRC → NSIDC DAAC (ftp pull)	1.75	1.41	1.25		

Requirements:

Source → Dest	Date	Mbps	Prev	Rating
GSFC → NSIDC	CY '12 –	8.42	27.6	Excellent
JPL → NSIDC	CY '12 –	0.16	0.2	Excellent
GHRC → NSIDC	CY '12 –	0.46	0.5	Excellent





Comments: GSFC → NSIDC S4PA: Thruput dropped from GSFC-EDOS and MODAPS-PDR, but remained stable from GES DISC and GSFC-ISIPS. Note that all these nodes are on EBnet at GSFC.

The rating is based on testing from the GES DISC server to the NSIDC DAAC. The requirement was reduced in May '09 from 34.5 mbps (and was 64 mbps in April '08).

The integrated thruput from GES DISC remains more than 3 x the requirement, so the rating remains “**Excellent**”. The 1.3 mbps average user flow was below typical, and was only 15% of the newly reduced requirement (which includes reprocessing).

JPL PODAAC → NSIDC S4PA: The requirement was reduced from 1.34 mbps in May '09. Thruput from PODAAC to NSIDC dropped from over 300 mbps previously; it had been mostly stable since testing was moved to use Internet2 in September '09; the rating remains “**Excellent**”.

GHRC, GHRC-ftp → NSIDC S4PA: GHRC (NSSTC, UAH, Huntsville, AL) sends AMSR-E data to NSIDC via NLR / Internet2. Thruput from GHRC experienced a drop (similar to the other drops above) at the end of May. The rating is based on reverse nuttcp testing. The median nuttcp thruput remained more than 3x the 0.46 mbps requirement, so the rating remains “**Excellent**”. User flow averaged 220 kbps this month, consistent with the requirement.





5) Boulder CO sites (Continued):**5.1) NSIDC:** (Continued):**Test Results: NSIDC SIDADS, NSIDC-PTH**

Source → Dest	Medians of daily tests (mbps)		
	Best	Median	Worst
GSFC-ENPL → NSIDC-SIDADS	188.9	183.0	129.3
GSFC-NISN → NSIDC-SIDADS	181.4	176.0	148.2
ESDIS-PTH → NSIDC-PTH	85.3	77.2	59.0
MODAPS-PDR → NSIDC-PTH	20.2	17.9	16.3
JPL PTH → NSIDC-PTH	88.7	84.0	55.5

GSFC → NSIDC-SIDADS: The performance to SIDADS via NISN and Internet2 was very stable this month – **no drop was observed**.

NSIDC-PTH: Thruput to NSIDC-PTH dropped at the end of May (similar to the drop to S4PA) from MODAPS-PDR, but was steady from ESDIS-PTH and JPL PTH. It has been requested to upgrade NSIDC-PTH from its Fast-E to a Gig-E interface.

**5.2) LASP:**

Ratings: GSFC ↔ LASP: Continued **Excellent**

Web Page: <http://ensight.eos.nasa.gov/Organizations/production/LASP.shtml>

Test Results:

Source → Dest	Medians of daily tests (mbps)		
	Best	Median	Worst
ESDIS-PTH → LASP blue (scp)	3.74	3.40	2.79
GES DISC → LASP blue (iperf)	7.71	6.41	4.81
LASP → GES DISC	9.34	9.34	8.37



Requirement:

Source → Dest	Date	Mbps	Rating
LASP → GES DISC	CY '10 -	0.016	Excellent

Comments: In January '11, LASP's connection to NISN PIP was rerouted: it previously was 100 mbps from CU-ITS via NSIDC; this was changed to a 10 mbps connection to the NISN POP in Denver.

Thruput from GES DISC to LASP improved in late April with a reduction in EBnet packet loss. SCP testing from ESDIS-PTH was very stable.

Thruput from LASP to GES DISC was also very stable, and well over 3x the requirement, so the rating remains "**Excellent**".


**5.3: UCB:**

Web Pages <http://ensight.eos.nasa.gov/Organizations/daac/UCB.shtml>

Test Results:

Source	Medians of daily tests (mbps)		
	Best	Median	Worst
GSFC-ENPL-10G	4194.8	3931.0	2909.9

Comments: Testing was added in April to a 10 gig connected test node at UCB. The route is via Internet2 to FRGP, similar to NCAR, with similar performance, as well. The previously observed diurnal variation was no longer present as the students left campus.



5) Boulder CO sites (Continued):**5.4) NCAR:**

Ratings: LaRC → NCAR: Continued **Excellent**
 GSFC → NCAR: Continued **Excellent**

Web Pages <http://ensight.eos.nasa.gov/Missions/terra/NCAR.shtml>

Test Results:

Source	Medians of daily tests (mbps)		
	Best	Median	Worst
LaRC PTH	188.0	154.5	82.1
GSFC-ENPL-10G	5443.2	2800.1	1141.2
GSFC-ENPL-FE	98.8	97.7	62.3
GSFC-NISN	346.7	169.7	95.0

Requirement:

Source	Date	Mbps	Prev	Rating
LaRC	CY '12 -	0.044	0.1	Excellent
GSFC	CY '12 -	0.111	5.0	Excellent




Comments: NCAR has a SIPS for MOPITT (Terra, from LaRC), and has MOPITT and HIRDLS (Aura, from GSFC) QA requirements.

Testing was switched to NCAR's PerfSonar server in March '12 – testing was discontinued from LaRC ASDC at that time; testing from LaRC-PTH continued. This node is 10 gigabit capable. Performance from most nodes was similar to the previous test node, but somewhat noisier.

From LaRC: Thruput from LaRC-PTH was well above 3 x the modest requirement, so the rating remains “**Excellent**”.

From GSFC: From GSFC-NISN, the route is via NISN to the MAX (similar route but better performance than from LaRC PTH). Thruput dropped at the end of May, similar to NSIDC nodes – but remained well above 3 x the requirement, so the rating remains “**Excellent**”. The average user flow from GSFC this month was 2.6 mbps, above the typical value of recent months, with peaks about equal to the requirement.

From GSFC-ENPL-10G, with a 10 Gig-E interface, and a 10 gig connection to MAX, performance to NCAR's 10 Gig PerfSonar node gets over 5 gbps on peaks! Significant diurnal variation is no longer present, probably due to UCB students leaving campus.



6) Remote Sensing Systems (RSS):

Ratings: JPL → RSS: Continued

Excellent

RSS → GHRC: Continued

ExcellentWeb Page <http://ensight.eos.nasa.gov/Missions/aqua/RSS.shtml>**Test Results:**

Source → Dest	Medians of daily tests (mbps)		
	Best	Median	Worst
JPL PODAAC → RSS (Comcast)	48.1	18.8	0.9
RSS (Comcast) → GHRC (UAH)	5.19	3.67	0.80
RSS (Comcast) → GHRC (NISN)	3.70	2.67	0.41

Requirements:

Source → Dest	Date	Mbps	Prev	Rating
JPL PODAAC → RSS	CY '12 -	0.16	0.49	Excellent
RSS → GHRC	CY '12 -	0.32	0.34	Excellent

Comments: RSS (Santa Rosa, CA) is a SIPS for AMSR-E (Aqua), receiving L1 data from JAXA via JPL, and sending its processed L2 results to GHRC (aka NSSTC) (UAH, Huntsville, AL).

At the end of March, RSS switched its production node from the NISN SIP circuit (4 x T1s to NASA ARC -- total 6 mbps) to the Comcast circuit, rated at 50 mbps incoming, and 12 mbps outgoing (installed in April 2011). Testing via NISN was discontinued at that time. Testing from JPL PODAAC got much better results using the Comcast circuit than via NISN. The route from JPL is via Los Nettos, CENIC, peering with Comcast in LA.




On May 14, testing was switched from a linux test server at RSS which was outside the firewall, to the windows production server inside the RSS firewall. Performance dropped at that time, both from JPL to RSS, and from RSS to GHRC. In addition, the windows server does not provide outgoing packet loss information.

Performance from JPL PODAAC also began exhibiting significant (50:1) diurnal variation at that time (unlike other sources).

The median iperf remained more than 3 x the reduced requirement, so the rating remains **Excellent**.

RSS → GHRC: In addition, the new servers at RSS connected to the Comcast circuit allows "3rd party testing", as does the server at GHRC. Testing has therefore been initiated from RSS to GHRC, both to a UAH address and a NISN address at GHRC. Performance dropped on May 14 due to the server switch at RSS (above)

Although packet loss is high, either result yields a rating of **Excellent** re the 0.32 mbps requirement.



7) Wisconsin:Rating: ↓ **Good** → **Adequate**Web Pages <http://ensight.eos.nasa.gov/Missions/NPP/WISC.shtml>**Test Results:**

Source Node	Medians of daily tests (mbps)			User Flow	Integrated
	Best	Median	Worst		
NPP-SD3E	343.4	266.7	183.3	195.0	316.3
GSFC DISC	253.9	217.7	161.9		
GSFC ENPL	243.9	186.6	93.0		
LaRC ANGe	176.3	166.2	113.0		



Requirements:

Source Node	Date	mbps	Prev	Rating
NPP-SD3E	CY'12 -	237.2	237.2	Good
GSFC MODAPS	CY'12 -	21.9	16.5	Excellent
GSFC Combined	CY'12 -	259.1	253.7	Adequate
LaRC Combined	CY'12 -	n/a	7.9	Excellent

Comments: The Univ of Wisconsin is included in this Production report due to its function as Atmosphere PEATE for NPP. Wisconsin continues to be an SCF on the MODIS, CERES and AIRS teams.

GSFC: Thruput dropped from all EBnet sources (NPP-SD3E, GES DISC) on 29 February due to EBnet outgoing packet loss. Even so, the integrated thruput was more than 30% above the NPP requirement, rating "Good", but was not 30% above the GSFC combined requirement, dropping the overall rating to Adequate. From ENPL thruput was similar, and unaffected by the EBnet packet loss. User flow increased slightly, and is now consistent with the requirement (less contingency). The route from GSFC is via MAX to Internet2, peering with MREN in Chicago.

LaRC: Thruput from LaRC ANGe is very steady and well above the requirement, rating "Excellent". The route from LaRC is via NISN, peering with MREN in Chicago.



**8) KNMI:**Rating: ↓ **Excellent** → **Good**Web Pages http://ensight.eos.nasa.gov/Missions/aura/KNMI_ODPS.shtml**Test Results:**

Source → Dest	Medians of daily tests (mbps)			Reqmt
	Best	Median	Worst	
OMISIPS → KNMI-ODPS	56.0	35.0	22.5	13.4
GSFC-ENPL → KNMI-ODPS	659.0	371.5	259.2	

Comments: KNMI (DeBilt, Netherlands) is a SIPS and QA site for OMI (Aura). The route from GSFC is via MAX to Internet2, peering in DC with Géant's 10 gbps circuit to Frankfurt, then via Surfnets through Amsterdam.

The requirement was increased with the use of the database to 13.4 mbps, a much more realistic value than the previous 0.03 mbps. The rating is based on the results from OMISIPS at GSFC to the ODPS primary server at KNMI. Thruput dropped on 29 February due to EBnet outgoing packet loss. It remains more than the increased requirement, but by less than 3 x, so the rating drops to Good. Thruput was much higher from GSFC-ENPL (outside of EBnet), and would be rated Excellent.

The user flow, however, decreased this month, averaging only 1.8 mbps (was a typical 4.3 mbps last month).



9) JSpace - ERSD:

Ratings: **GSFC → ERSD: Continued Excellent**
ERSD → EROS: Continued Excellent
ERSD → JPL-ASTER-IST: Continued Excellent

Web Page: <http://ensight.eos.nasa.gov/Organizations/production/ERSDAC.shtml>

US ↔ JSpace - ERSD Test Results

Source → Dest	Medians of daily tests (mbps)			User Flow	Integrated
	Best	Median	Worst		
GSFC-EDOS → ERSD	73.8	40.7	8.5	4.3	42.5
GES DISC → ERSD	42.2	35.1	25.6		
GSFC ENPL (FE) → ERSD	93.3	92.6	91.6		
GSFC ENPL (GE) → ERSD	619.7	533.6	331.7		
ERSD → EROS	124.6	90.3	57.4	4.0	91.4
ERSD → JPL-ASTER IST	68.1	60.7	51.9		

Requirements:

Source → Dest	CY	Mbps	Prev	Rating
GSFC → ERSD	'12 -	6.75	5.4	Excellent
ERSD → JPL-ASTER IST	'12 -	0.31	0.31	Excellent
ERSD → EROS	'12 -	8.33	8.3	Excellent

Comments:

GSFC → ERSD: As of approximately 1 September '11, the ERSDAC test node is connected at 1 gbps – formerly was 100 mbps. The median throughput from most nodes improved. A new test from **GSFC ENPL** was able to get average throughput over 500 mbps. However, some nodes have been using QoS (HTB) to reduce loss previously seen in the 1 gig to 100 meg switch at Tokyo-XP – those nodes remain limited by their HTB settings, and did not see much improvement.





Throughput dropped from all EBnet sources (**GSFC-EDOS**, **GES DISC**) on 29 February due to EBnet outgoing packet loss. But throughput remains well above 3 x the reduced requirement, so the rating remains “**Excellent**”. The integrated chart shows that the user flow is mostly stable, and consistent with the requirement.

Throughput from **GES DISC** to ERSD did not improve with the Gig-E upgrade at ERSDAC. The **GES DISC** configuration is planned to be upgraded soon.

The FastE connected **GSFC-ENPL-FE** node is limited to 100 mbps by its own interface, and gets very steady throughput.

ERSD → JPL-ASTER-IST: The throughput remains very stable with the median well above the [unstated] requirement (IST requirements are generally 311 kbps), so the rating remains “**Excellent**”.

ERSD → EROS: The throughput improved with retuning in October '11, after the ERSDAC Gig-E upgrade; it remains well above the reduced requirement (was 26.8 mbps previously). The user flow was near normal this month. The median throughput is more than 3 x the reduced requirement, so the rating remains “**Excellent**”.



10) US \leftrightarrow JAXA

The JAXA test hosts at EOC Hatoyama were retired on March 31, 2009 (the end of the Japanese government's fiscal year). No additional testing is planned for AMSR or TRMM. [All testing to JAXA-TKSC for ALOS was terminated at the end of June '09.](#)

However, the user flow between GSFC and JAXA continues to be measured. As shown below, the user flow this month averaged 3.64 mbps from GSFC to JAXA (with many peak periods over 5 mbps), and 110 kbps from JAXA to GSFC (with 2 peaks to about 3 mbps, and many peaks over 500 kbps).

These values compare favorably to the new (database) requirements of 3.5 mbps to JAXA, and 0.16 mbps back to JPL. However, since no iperf tests are run, the true capability of the network cannot be determined, and therefore no rating is assigned.

